

### NORFFSWPP NORFOLK PREMIUM PACK CLIMBER

The components of this gym can be combined with others to create different play sets. This is the best order of assembly to create this specific set.

Read this sheet and all instructions included with the different parts before assembly.

See the Instructions and Owner's Manual included in carton 63089-116 for important safety information.

Dimensions of assembled package:  
11' 10" wide x 16' 1" deep x 11' 6" tall



#### Cartons for this Play Set:

1	63089-116	Norfolk II Box 1 (Hdwre & Instr)
1	63089-216	Norfolk II Box 2
1	63089-316	Norfolk II Box 3
1	63089-416	Norfolk II Roof
1	63089-606	Norfolk II Cargo Net
1	63045-505	Norfolk Tire Swing (Hardware)
1	8364-400	10ft. Scoop Slide
1	SH922-800Q	Ramp (Hdwre & Instr)
1	SH304-101Q	Pinnacle Wall (Hdwre & Instr)



- Assemble the Norfolk tower. Instructions and hardware are in the cartons noted above right.
- Norfolk step 30. Wait to install front wall slat until the ramp and slide are in place.
- Set the ramp and slide in place. Check spacing.
- Install the slide mount and slide using the method shown in steps 37 and 38 of the Norfolk instructions.
- Install the Ramp (SH922-800Q). Add a single wall slat between the ramp and the slide.
- Install the Pinnacle Climber (SH304-101Q) on the back of the tower.
- Double-check all fasteners are secure and all recessed hardware is covered by hole caps.