

Cartons for this Play Set:

1	63006-421	Williamsburg Box 1 (Hardware)
1	63006-422	Williamsburg Box 2
1	63006-423	Williamsburg Box 3
1	63006-424	Williamsburg Tent (Hdwre & Instr)
1	SH946-102	Access Ladder, 5ft
1	63058-202	4 Position Swing Beam
1	63059-212	7ft Swing Beam Legs (Hdwre & Instr)
1	31820-102	Swing Mount
1	50546-777	3 Swings, 1 Trapeze
1	8364-400	10 ft Scoop Slide, Green
1	SD920-800Q	Wmsbg Picnic Table (Hdwre & Instr)
1	AH201-102Q	Rock Climbing Wall (Hdwre & Instr)
1	63079-102	Monkey Bars (Hdwre & Instr)

Dimensions of assembled package:
19' 8" wide x 15' 7" deep x 10' 7" tall



The components of this gym can be combined with others to create different play sets. This is the best order of assembly to create this specific set.

Read this sheet and all instructions included with the different parts before assembly.

See the Instructions and Owner's Manual included in carton 63006-424 for important safety information.



- Start by assembling the Williamsburg tower. Instructions and hardware are in the cartons noted above right.
- Wait to install the Access Ladder, Slide, and Wall Slats until after the rest of the play set is complete.
- On step 19 be sure to install the swing mount on the side shown above.
- Wmsburg step 20. Do not install the safety rail. It will be used for the picnic table.
- Install the swing beam. Instructions and hardware are in the 7 ft Swing Beam Leg carton (63059-212).
- Install the Picnic Table (SD920-800Q).
- Install the Rock Climber (AH201-102Q).
- Install the Monkey Bars (63079-102). Mount one side directly to the corner post as shown above.
- Install the slide mount and slide using the method shown in steps 26 and 27 of the Williamsburg instructions.
- Secure the access ladder on the back of the gym using the method shown in step 18 of the Williamsburg instructions.
- Install the wall slats in the positions shown above, using the methods from the Williamsburg Instructions. Gaps must be narrower than 3-1/2" or wider than 9" to prevent potential head entrapment.
- Mount the hand grips to the entrance wall slats.
- Double-check all fasteners are secure and all recessed hardware is covered by hole caps.