

Cartons for this Play Set:

| | | |
|---|------------|-------------------------------------|
| 1 | 63006-421 | Williamsburg Box 1 (Hardware) |
| 1 | 63006-422 | Williamsburg Box 2 |
| 1 | 63006-423 | Williamsburg Box 3 |
| 1 | 63006-445 | Williamsburg Roof (Hdwre & Instr) |
| 1 | SH946-102 | Access Ladder, 5ft |
| 1 | 63058-202 | 4 Position Swing Beam |
| 1 | 63060-222 | 9ft Swing Beam Legs (Hdwre & Instr) |
| 1 | 50546-777 | 3 Swings, 1 Trapeze |
| 1 | 15166-400 | 10 ft. Super Wave Slide |
| 1 | AG942-400 | Access Ladd Handles (Hdwre & Instr) |
| 1 | AG943-400 | Slide Handle (Hdwre & Instr) |
| 1 | SM964-402 | Gable Fans (Hdwre & Instr) |
| 1 | SM963-402 | Dormer (Hdwre & Instr) |
| 1 | AH201-102Q | Rock Climbing Wall (Hdwre & Instr) |
| 1 | SC908-800Q | Wmsburg Play Floor (Hdwre & Instr) |
| 2 | 40456-402 | End Window Panel |
| 1 | 40457-402 | Side Window Panel |
| 1 | 40458-402 | Side Door Panel (Hdwre & Instr) |

Dimensions of assembled package:
17' 0" wide x 15' 6" deep x 11' 6" tall



The components of this gym can be combined with others to create different play sets. This is the best order of assembly to create this specific set.

Read this sheet and all instructions included with the different parts before assembly.

See the Instructions and Owner's Manual included in carton 63006-445 for important safety information.

- Start by assembling the Williamsburg tower. Instructions and hardware are in the cartons noted above right.
- Wait to install the Access Ladder, Slide, and Wall Slats until after the rest of the play set is complete.
- Skip steps 7 & 8. Do not install the angle braces. They interfere with the clubhouse panels.
- Skip steps 20 & 21.
- Install the swing beam. Instructions and hardware are in the 9' Swing Beam Leg Carton (63060-222).
- Install the Play Floor (SC908-800Q).
- Install the Clubhouse Panels. Instructions and hardware are attached to the door panel (40458-402).
- Install the Dormer (SM963-402).
- Install the Gable Fans (SM964-402).
- Install the Rock Climbing Wall (AH201-102Q) in the position shown.
- Set the ladder and slide as shown above. Check spacing.
- Fasten access brackets to the **inside** of the ladder rails. Secure the access ladder using the method shown in step 18 of the Williamsburg instructions.
- Mount the Access Ladder Handles (AG942-400).



- Install the slide mount and slide using the method shown in steps 27 and 28 of the Williamsburg instructions.
- Install the wall slats in the positions shown above, using the methods from the Williamsburg Instructions. Gaps must be narrower than 3-1/2" or wider than 9" to prevent potential head entrapment.
- Mount one hand grip to the entrance wall slat between the ladder and the slide. Mount the other hand grip to the adjacent post at the same height, using 1/4 x 1-1/2" lag screws and 1/4" flat washers. Drill 3/16" diameter pilot holes for the lag screws.
- Mount the Slide Handle (AG943-400) above the slide.
- Double-check all fasteners are secure and all recessed hardware is covered by hole caps.