



Dimensions of assembled package:  
20' 7" wide x 16' 8" deep x 11' 6" tall

The components of this gym can be combined with others to create different play sets. This is the best order of assembly to create this specific set. Read this sheet and all instructions included with the different parts before assembly. See the Instructions and Owner's Manual included in carton 63062-222 for important safety information.

### Cartons for this Play Set:

1 63062-211	Yorktown 1 (Hardware)	1 15166-400	10 ft. Super Wave Slide
1 63062-222	Yorktown 2 (Instructions)	1 63058-202	4 Position Swing Beam
1 63007-421	Lexington Gym 1 (Hardware)	1 63076-303	9ft Swing Beam Legs (Hdwre & Instr)
1 63007-422	Lexington Gym 2	1 50546-777	3 Swings, 1 Trapeze
1 63062-301	Yorktown Wood Roof (Hardware)	1 63081-102	Ice Cream Stand (Hdwre & Instr)
1 SH946-102	Access Ladder 5ft.	1 63079-102	Monkey Bars (Hdwre & Instr)
1 SM963-402	Dormer Brown (Hdwre & Instr)	1 SC909-800Q	Lexington Play Walls (Hdwre & Instr)
1 SM964-402	Gable Fans (Hdwre & Instr)	1 SC910-800Q	Lexington Play Floor (Hdwre & Instr)
2 40456-402	End Panel Assembly	1 AG942-400	Access Ladder Handles (Hdwre & Instr)
1 40459-402	Double Window Panel	1 AG943-400	Slide Handle (Hdwre & Instr)
1 40460-402	Door & Window Panel (Hdwre & Instr)	1 AA917-603	Fireman's Pole (Hdwre & Instr)

- Start by assembling the Yorktown tower. Instructions are in carton 63062-222. Other instructions and hardware are in the cartons noted at left.
- Yorktown step 12. Omit the angle brace on the corner where the chalkboard will mount when assembling the ice cream stand.
- Yorktown step 19. The 9ft Beam will be mounted in the position pictured above. Parallel to the roof.
- Wait to install the Access Ladder, Slide, and Wall Slats until after the rest of the play set is complete.
- Install the 9ft Swing Beam. Instructions are in carton 63076-303.
- Install the Lexington Play Floor (SC910-800Q).
- Install the Ice Cream Stand (63081-102) on the end of the tower opposite the swings.
- Install the Play Walls (SC909-800Q) along the back and swing side of the main tower.
- Install the Monkey Bars (63079-102) in the position shown.
- Mount one ladder rail directly to the post.
- Install the Fireman's Pole (AA917-603) to the same post.
- Install the slide mount and slide using the method shown in steps 36 and 37 of the Yorktown instructions.
- Secure the access ladder in the position shown using the method shown in step 35 of the Yorktown instructions.
- Fasten Access Ladder Handles (AG942-400) to the ladder.
- Install the slide mount and slide using the method shown in steps 36 and 37 of the Yorktown instructions.
- Install wall slats in the positions shown using methods from the Yorktown instructions. Gaps must be narrower than 3-1/2" or wider than 9" to prevent potential head entrapment. Leave space to access fireman's pole.
- Mount one hand grip to each entrance wall slat.
- Mount the Slide Handle (AG943-400) above the Super Wave Slide.
- Double-check all fasteners are secure and all recessed hardware is covered by hole caps.